

AS-7.5 & AS-10 SPECS 36" HYDRAULIC INSERTION PRESS

The Auto-Sert 36" Hydraulic Insertion Press offers all the features of the Auto-Sert 20" with the ability to handle larger applications. It can be easily fitted with a moving brush table to both reduce operator fatigue and improve the overall safety. We think you'll agree that these machines are on the leading edge of technology in hardware insertion, and are unrivaled in design and quality. Available in 7.5 and 10 ton capacity.

DESCRIPTION	AS-7.5/36" THROAT	AS-10/36" THROAT
TONNAGE CAPACITY	Minimum 350 lbs. Maximum 15,000 lbs.	Minimum 350 lbs. Maximum 20,500 lbs.
THROAT DEPTH TO BACK	36" (914.4mm)	36" (914.4mm)
THROAT DEPTH TO TOP	20" (508mm)	20" (508mm)
RAM STROKE	6" (152mm)	6" (152mm)
HYDRAULIC PRESSURE	Minimum 40 P.S.I. Maximum 3,000 P.S.I.	Minimum 40 P.S.I. Maximum 3,000 P.S.I.
OIL RESERVOIR CAPACITY	12 gallons (45.42 lit.)	12 gallons (45.42 lit.)
ELECTRICAL SPECS	208/230/415/460/575 V 3 Phase 50/60 Hz	208/230/415/460/575 V 3 Phase 50/60 Hz
HEIGHT	79" (2007mm)	79" (2007mm)
WIDTH	36" (914mm)	36" (914mm)
DEPTH	64" (1625.6mm)	64" (1625.6mm)
WEIGHT	2500 lbs. (1132.5kgs.)	2500 lbs. (1132.5kgs.)



Auto-Sert AS-7.5 - 36 in. Hardware Insertion Press